

Working radius (m)	Boom length (m)														
	12.20	15.25	18.30	21.35	24.40	27.45	30.50	33.55	36.60	39.65	42.70	45.75	48.80	51.85	54.85
3.7	70.0														
4.0	68.0	68.0													
4.5	55.0	54.4													
5.0	45.0	45.0	45.0												
5.5	38.8	38.8	38.8	38.8											
6.0	33.6	33.5	34.4	33.5	33.5										
7.0	26.7	26.6	26.5	26.5	26.5	26.4	26.2								
8.0	22.1	22.0	21.9	21.8	21.7	21.7	21.6	21.5	21.4						
9.0	18.9	18.8	18.7	18.6	18.5	18.4	18.3	18.3	18.2	18.2	18.1				
10.0	16.5	16.4	16.3	16.2	16.1	16.0	15.9	15.9	15.8	15.8	15.7	15.6	15.2		
12.0	13.4/11.7	12.8	12.7	12.6	12.5	12.4	12.3	12.3	12.3	12.2	12.1	12.1	12.0	11.6	
14.0		10.5	10.4	10.3	10.2	10.1	10.0	9.9	9.8	9.7	9.6	9.5	9.4	9.3	9.2
16.0			8.7	8.6	8.5	8.4	8.3	8.2	8.1	8.0	7.9	7.8	7.7	7.6	7.5
18.0				7.4	7.3	7.2	7.1	7.0	6.9	6.8	6.7	6.6	6.5	6.4	6.3
20.0				6.6/19.6	6.3	6.2	6.1	6.0	-5.9	5.8	5.7	5.6	5.5	5.4	5.3
22.0					5.5	5.4	5.3	5.2	5.1	5.0	4.9	4.8	4.7	4.6	4.5
24.0						4.7	4.6	4.5	4.4	4.3	4.2	4.1	4.0	3.9	3.8
26.0						4.3/24.9	4.1	4.0	3.9	3.8	3.7	3.6	3.5	3.4	3.3
28.0							3.7/27.5	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9
30.0								3.2	3.1	3.0	2.9	2.8	2.7	2.6	2.5
32.0									2.8	2.7	2.6	2.5	2.4	2.3	2.2
34.0										2.5	2.4	2.3	2.2	2.1	1.0
36.0										2.2/35.4	2.2	2.1	2.0	1.9	1.8
38.0											2.0	1.9	1.8	1.7	1.6